



XIAMEN JOINT TECH. CO., LTD.

JOINT TECH, BORN FOR GREEN ENERGY SOLUTIONS

✉ lyth@jointevse.com

🌐 www.jointcharging.com

📍 No. 268 Houxiang Rd, Xinyang Industrial Park, Haicang District, Xiamen, Fujian, China

EVCP4

A PERFECT EXAMPLE OF TECHNOLOGICAL INTEGRATION,
EFFICIENCY AND MAXIMUM INNOVATION



INNOVATION

The integration of EV charging, LED lighting and display advertising service.



STRUCTURE

Consists of a pole, LED lighting, integrated charging post and advertising screen.



VERSATILE

Available in different styles to be able to fit into any street and urban context.



QUICK

Up to 22kW of charging capacity. Interface IEC 62196 compliant, T2 socket.



OPEN

Possibility to insert any lamp or light source.



INSTALLATION

Saves time and money through modular assembly.



DATASHEET

EV Charger		JNT-EVCP4/AC07	JNT-EVCP4/AC22
Input	Input Rating	230Vac ± 10% (1-phase)	400Vac ± 10% (3-phase)
	Input Current	32A	
	Frequency	50/60Hz	
Output	Output Current	32A	
User Authentication		RFID (ISO 14443)	
External		LAN + Wi-Fi (optional) or 4G (optional)	
Internal		OCPP 1.6 JSON	
Operating Temperature		-30°C ~ 50°C	
Humidity		5% ~ 95%	
Altitude		≦ 2000m	
IP Level		IP54	
Charging Outlet		IEC 62196-2 Compliant, Type 2 Socket	
Multiple Protection		UVP, OVP, RCD (Type A + DC 6mA), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection	
Warranty		2 years	

Dimension	400x800mm
IP Level	IP65
Frame Material	Cast Aluminum
Voltage	AC 220V/110V ± 10%, 47-63Hz.
Operating Temperature	-40°C ~ 80°C
Humidity	10% ~ 90%RH
Protection	Leakage Protection, Short-circuit Protection, Surge Protection
Warranty	1 year

LED Light

Wattage	60W	80W	100W	120W	150W	200W	240W	320W
Voltage	100V-277Vac / 277V-480Vac							
CCT	2200K, 3000K, 4000K, 5000K, 5700K							
Control	0-10V Dimming / Network Ready Control							
IP Rating	IP66							
CRI	70+							
Working Temperature	-40°C ~ 50°C							
Warranty	5 years							

OCPP 1.6J, CONNECTED SUCCESSFULLY WITH 50+ GLOBAL EVC PLATFORMS

