



XIAMEN JOINT TECH. CO., LTD.

JOINT TECH, BORN FOR SUSTAINABLE ENERGY

🌐 www.jointcharging.com

✉ info@jointcharging.com

📍 No.98, South Dongfu Road, Haicang District, Xiamen, China

EVC33 / Mode 3

UP TO 22KW




BUILT-IN PEN

No need for earth rods with built in O-PEN conductor protection



TAMPER-PROTECTION

To protect the internal components



SECURE COMMUNICATION

Are encrypted using industry standard protocols



OCPP-COMPLIANT

OCPP1.6J, OCPP2.0.1 Updatable



DYNAMIC LOAD MANAGEMENT

Protect the property's fuse and reduce cost for power upgrades



INSTALLATION FRIENDLY

Slot-in wiring from up and down, easy & simple



Color: Black White



**REMOVABLE
CUSTOM FASCIA**



DATASHEET

Model No.	EVC33/AC07	EVC33/AC11	EVC33/AC22
Voltage	230Vac±10%	400Vac±10%	
Amperage/Power	32A/7KW	16A/11KW	32A/22KW
AC Power Frequency	50-60Hz		
User Authentication	RFID ISO14443		
Connectivity	LAN & Wi-Fi, 4G optional		
	OCPP1.6J, OCPP2.0.1 updatable		
Charging Interface	IEC 62196-2 Compliant, Type 2		
Safety Compliance	IEC61851-1, IEC61851-21-2		
Multiple Protection	UVP, OVP, RCD (TypeA+DC6mA), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection		
Operating Temperature	-30°C ~ 50°C		
IP Level	IP54		
IK Rating	IK08		
Relative Humidity	Up to 95% non-condensing		
Cable Length	5 meter (7.5 meter optional)		
Net Weight	5.5kg		
Gross Weight	7.8kg		
Product Dimensions	345*192*149mm		
Package Dimensions	415*305*295mm		