


GREEN ENERGY READILY AVAILABLE



KEY FEATURES AND BENEFITS



FITS OVER 99.5% OF POPULAR CAR MODELS

Based on AI algorithm adaptive matching mainstream electric models, worry-free charging.



MULTI-SCENE INTELLIGENT CHARGING

Plug and charge / RFID card / OCPP control three charging methods, independent authorization, not afraid of being stolen.



LEAN OPERATION MANAGEMENT OF VEHICLES, CHARGING STATIONS, AND PLATFORMS

Compatible with 50+ CPO platforms in the world, OCPP 1.6J help you connect EV charger to the cloud, Cyber Security security.



SMART DYNAMIC LOAD BALANCING

Intelligent adjustment of power output according to power grid load fluctuations, all-round protection of vehicles.



INTELLIGENT IOT DEVICE MONITORING

Devices connect with WIFI & Bluetooth, real-time device monitoring via app, remote OTA updates.

SPECIFICATIONS



EVC10

POWER		
Input Rating	230V±10% (Single-Phase)	400V±10% (Three-Phase)
Output Current&Power	7KW (32A)	11KW (16A) / 22KW (32A)
Power Wiring	L / N / PE	L1 / L2 / L3 / N / PE
Input Cord	Hardwire	
Mains frequency	50 / 60 Hz	
Connector Point	IEC 62196-2 Compliant, Type 2 with 5m cable / 7m (Optional)	
Ground Fault Detection	Built-in RCD (DC 6 mA)	
Protection	UVP, OVP, RCD , SPD, Ground Fault Protection, OCP, OTP, Control Pilot Fault Protection	
USER INTERFACE		
Status Indication	LED indication	
Screen	4.3' screen	
Language	English	
Connectivity	Bluetooth, Wi-Fi, Ethernet, 4G (Optional)	
Communication Protocols	Compatible with multiple CPOs	
Function Available	CT-Clamp	
User Authentication	Plug & Charge , RFID Card、 CPOs	
Card Reader	ISO 14443 A/B	
Software Update	OTA	
CERTIFICATION & STANDARDS		
Safety & Compliance	EN 62196-2:2017-06、 EN IEC 61851-1:2019-10、 EN IEC 61851-21-2:2021-09、 EN 62196-1:2015-05、 EN 61008-1 and IEC 62955	
Certification	CE / CB	
Warranty	36 months	
GENERAL		
Button	Emergency Button	
Enclosure Rating	IK08; IP54 (socket); IP65 (cable)	
Operating Altitude	< 2000m	
Operating Temperature	-30°C ~ +50°C	
Operating Humidity	5~95%	
Mounting	Wall mount / Pedestal (Optional)	
Color	Black / Silver	
Product Dimensions	351mm*250mm*130mm (Cable) / 351mm*250mm*155mm (Socket)	
Package Dimensions	444mm*324mm*215mm (Socket) / 497mm*348mm*267mm (Cable)	

CERTIFICATION

 **35000m²**
Factory Size

 **200+**
Total Employees

 **120+**
Certifications & Patents

 **OCPP2.0.1**
ISO15118

Joint
@ Sustainable Energy

SUSTAINABLE ENERGY

 <https://jointcharging.com>

 info@jointcharging.com

 No.98, South Dongfu Road, Haicang District, Xiamen, PRC